



Halogen Low Voltage

13163 ELC/5H 250W GX5.3 24V 1CT/24

The long lifetime of most of the Halogen Low Voltage lamps is further extended by the unique P3 technology developed by Philips. This allows the lamp to be used at higher temperatures, thereby extending the lamp's lifetime, reducing early failures, and resulting in fewer maintenance man hour costs. P3 also ensures consistency of high-quality light output, and allows the lamp to be used in any burning position, which enables more compact fixture designs. In addition, the compact filament produces a clean white light and high beam intensity for true natural colors on stage and without any hotspots.


Product data

General Information		Controls and Dimming	
Cap-Base	GX5.3 [GX5.3]	Dimmable	Yes
Philips Code	13163	Mechanical and Housing	
ANSI Code	ELC-5H	Bulb Material	Quartz-UV Open
LIF Code	-	Reflector Finish	Smooth
Operating Position	S90 [Standing +/-90D or Base Down (BDH)]	Filament Dimensions WxH	-
Main Application	Projection	Luminaire Design Requirements	
Life To 50% Failures (Nom)	500 h	Bulb Temperature (Max)	900 °C
Light Technical		Pinch Temperature (Max)	400 °C
Correlated Color Temperature (Nom)	3400 K	Working Distance WD	32 mm
Color Rendering Index (Nom)	100	Product Data	
Operating and Electrical		Full product code	871150041347530
Power (Rated) (Nom)	250 W	Order product name	13163 ELC/5H 250W GX5.3 24V 1CT/24
Voltage (Nom)	24 V	EAN/UPC - Product	8711500413475
		Order code	924862720540
		Numerator - Quantity Per Pack	1

Halogen Low Voltage

Numerator - Packs per outer box	24
Material Nr. (12NC)	924862720540
Net Weight (Piece)	0.024 kg

Dimensional drawing



ELC/5H 250W GX5.3 24V

Product	D (max)	C (max)
13163 ELC/5H 250W GX5.3 24V 1CT/24	50 mm	44.5 mm

