

Name	SC-Spirit XXL
Properties	OFC oxygen free copper
Properties	Analog
Application area	Mobile outdoor / indoor
Application area	Stage / live
Application area	Studio / Broadcast
Application	Instrument Cable
Colour	transparent
Colour	brown
Colour	black
Colour detailed	brown
Colour detailed	black
Colour detailed	transparent
Signal transmission	asymmetrical
Construction	LI2Y(LS)CY 1x0,75mm ²
Jacket material	PVC
Jacket material (audio)	transp. PVC
Jacket Ø [mm]	6,80
Number of Channels (audio)	1
Inner conductor (audio)	1
Inner conductor (audio) [mm ²]	0,75
Inner conductor Ø (audio) [mm]	0,98
AWG (audio)	18
Shielding	Copper spiral tin-plated + semiconductor
Copper strands (audio)	42
Copper strand Ø (audio) [mm]	0,15
Conductor insulation material	Foam / Skin-PE
Conductor insulation Ø [mm]	3,10
Weight per 1 m [g]	52
UV-resistant	yes
Fire load per m [kWh]	0,26
Style variant	round
Shielding factor [%]	100
Packing	100 m spool
Temperature min. [°C]	-30
Temperature max. [°C]	70
Width [mm]	6,8
Height [mm]	6,8
Capac. cond./shield. per 1 m (audio) [pF]	86
Capacity wire/electric screen at 1 ft. (audio) [pF]	26,2128
Insulation resist. per 1 km [GΩ]	0,05
Insulation resist. per 1000 feet [GΩ]	0,0152
Insulation resist. per 1 km (audio) [GΩ]	0,05
Insulation resist. per 1000 feet (audio) [GΩ]	0,0152
Conductor resistance per 1 km [Ω]	25
Conductor resistance per 1000 ft. [Ω]	7,62
EAN	4049371004626