

Name	SC-Cicada SO-D14
Properties	Analog
Properties	OFC oxygen free copper
Properties	PUR
Application area	Installation
Application	Patch & Microphone Cable
Colour	black
Colour detailed	black
Signal transmission	symmetrical
Construction	(2LI2Y0,14mm²)DY
Jacket material	PUR Master-Blend
Jacket Ø [mm]	2,60
Number of Channels (audio)	1
Inner conductor (audio)	2
Inner conductor (audio) [mm²]	0,14
Inner conductor Ø (audio) [mm]	0,42
AWG (audio)	26
Shielding	Copper spiral shielding + filler strand, tin-plated (0.22 mm²)
Copper strands (audio)	18
Copper strand Ø (audio) [mm]	0,10
Conductor insulation material	PE
Conductor insulation Ø [mm]	0,90
Weight per 1 m [g]	13
UV-resistant	yes
Fire load per m [kWh]	0,08
Style variant	round
Shielding factor [%]	95
Packing	100 m spool
Temperature min. [°C]	-30
Temperature max. [°C]	70
Width [mm]	2,6
Height [mm]	2,6
Capac. cond./cond. per 1 m (audio) [pF]	65
Capacity wire/wire at 1 ft. (audio) [pF]	19,812
Capac. cond./shield. per 1 m (audio) [pF]	120
Capacity wire/electic screen at 1 ft. (audio) [pF]	36,576
Insulation resist. per 1 km [GΩ]	1
Insulation resist. per 1000 feet [GΩ]	0,3048
Insulation resist. per 1 km (audio) [GΩ]	1
Insulation resist. per 1000 feet (audio) [GΩ]	0,3048
Conductor resistance per 1 km [Ω]	148
Conductor resistance per 1000 ft. [Ω]	45,1104
Shield. resistance per 1 km [Ω]	30
Shield. resistance per 1000 ft. [Ω]	9,144
EAN	4049371002066