

Name	SC-Source MKII
Properties	Analog
Properties	OFC oxygen free copper
Application area	Studio / Broadcast
Application area	Mobile outdoor / indoor
Application area	ELA 100 V
Application area	Stage / live
Application area	Installation
Application	Microphone Cable
Colour	black
Colour detailed	black
Signal transmission	symmetrical
Construction	(2LI2Y0,25mm²)(ST)DY
Jacket material	PVC
Jacket Ø [mm]	6,50
Number of Channels (audio)	1
Inner conductor (audio)	2
Inner conductor (audio) [mm²]	0,25
Inner conductor Ø (audio) [mm]	0,56
AWG (audio)	23
Shielding	copper spiral sleeve tin-plated 95 % + AL-fleece
Copper strands (audio)	128
Copper strand Ø (audio) [mm]	0,05
Conductor insulation material	PE
Conductor insulation Ø [mm]	1,55
Weight per 1 m [g]	48
UV-resistant	yes
Fire load per m [kWh]	0,21
Style variant	round
Shielding factor [%]	100
Packing	100 m spool
Packing	500 m spool
Temperature min. [°C]	-25
Temperature max. [°C]	70
Width [mm]	6,5
Height [mm]	6,5
Capac. cond./cond. per 1 m (audio) [pF]	60
Capacity wire/wire at 1 ft. (audio) [pF]	18,288
Capac. cond./shield. per 1 m (audio) [pF]	110
Capacity wire/electric screen at 1 ft. (audio) [pF]	33,528
Insulation resist. per 1 km [GΩ]	0,2
Insulation resist. per 1000 feet [GΩ]	0,061
Insulation resist. per 1 km (audio) [GΩ]	0,2
Insulation resist. per 1000 feet (audio) [GΩ]	0,061
Conductor resistance per 1 km [Ω]	78
Conductor resistance per 1000 ft. [Ω]	23,7744
Shield. resistance per 1 km [Ω]	25
Shield. resistance per 1000 ft. [Ω]	7,62
EAN	4049371004169