

HMI 1200 W/DXS

HMI | Metal halide lamps, double-ended



Technical data


Electrical data

| | |
|-----------------|-----------|
| Nominal wattage | 1200.00 W |
| Lamp wattage | 1200 W |
| Lamp voltage | 100 V |
| Nominal current | 13.8 A |
| Lamp current | 13.8 A |

Photometrical data

| | |
|--------------------------|--------|
| Color temperature | 6000 K |
| Color rendering index Ra | > 90 |

Dimensions & weight



| | |
|---|-----------|
| Diameter | 27.0 mm |
| Length | 220.0 mm |
| Mounting length | 180.0 mm |
| Length with base excl. base pins/connection | 180.00 mm |

Lifespan

| | |
|----------|--------|
| Lifespan | 1000 h |
|----------|--------|

Additional product data

| | |
|-----------------------------|---------|
| Base (standard designation) | SFc15.5 |
|-----------------------------|---------|

Capabilities

| | |
|------------------|-----|
| Burning position | Any |
|------------------|-----|

Certificates & standards

Product datasheet

| | |
|--------------------|---|
| EEI – Energy Label | B |
|--------------------|---|

Country specific information

| Product code | METEL code | SEG-No. | STK number | UK Org |
|---------------|---------------|---------|------------|--------|
| 4008321931153 | OSRHMI1200DXS | - | 4836421 | - |

Product datasheet

Safety advice

Because of their high luminance, UV radiation and high internal pressure during operation, HMI lamps may only be operated in enclosed lamp casings specially constructed for the purpose. Appropriate filters must ensure that UV radiation is reduced to an acceptable level. Mercury is released if the lamp breaks. Special safety precautions must be taken. Information on safety and handling is available on request or can be found in the leaflet included with the lamp or in the operating instructions.

Logistical Data

| Product code | Product description | Packaging unit (Pieces/Unit) | Dimensions (length x width x height) | Volume | Gross weight |
|---------------|---------------------|---------------------------------|---|----------------------|--------------|
| 4008321931153 | HMI 1200 W/DXS | Shipping carton box 1 | 305 mm x 82 mm x 115 mm | 2.88 dm ³ | 253.00 g |
| 4052899501355 | HMI 1200 W/DXS | Shipping carton box 10 | - x - x - | | |

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.