

MSR Gold™ FastFit

MSR Gold™ 700 FastFit 1CT/4

All lamps burn out eventually, but when this happens with single ended MSR Gold™ FastFit, it is replaced in seconds – thanks to the specially designed lamp base and lamp holder. This lamp provides a high beam intensity of pure, white light for a truly illuminating performance, while the gold-plated caps provide superior heat protection and prevent premature failure. P3 technology allows use in any position and at higher temperatures, further extending lamp life and consistency of high-quality light output. Also, because the FastFit design is applied to Philips Halogen lamps, switching between lamp technologies can be done quickly and easily. The Philips MSR Gold™ FastFit can be operated in a lamp wattage range between 700W and 2500W.

Product data


General Information		Operating and Electrical	
Cap-Base	PGJX50 [PGJX50]	Power (Rated) (Nom)	700 W
Operating Position	UNIVERSAL [Any or Universal (U)]	Lamp Current (Nom)	10.2 A
Main Application	Entertainment	Ignition Supply Voltage (Min)	198 V
Life To 50% Failures (Nom)	750 h		
System Description	FastFit		
Light Technical		Controls and Dimming	
Luminous Flux (Min)	45500 lm	Dimmable	Yes
Luminous Flux (Nom)	50000 lm		
Chromaticity Coordinate X (Nom)	327	Mechanical and Housing	
Chromaticity Coordinate Y (Nom)	336	Cap-Base Information	PGJX50
Correlated Color Temperature (Nom)	6000 K		
Luminous Efficacy (rated) (Nom)	71 lm/W	Luminaire Design Requirements	
Color Rendering Index (Nom)	80	Bulb Temperature (Max)	950 °C
		Pinch Temperature (Max)	500 °C
Product Data			
Full product code		871829122119700	

MSR Gold™ FastFit

Order product name	MSR Gold™ 700 FastFit 1CT/4
EAN/UPC - Product	8718291221197
Order code	928106005115
Numerator - Quantity Per Pack	1
Numerator - Packs per outer box	4

Material Nr. (12NC)	928106005115
Net Weight (Piece)	0.100 kg

Dimensional drawing



MSR GOLD 700 FastFit

Product	D	O	L	L	L	C	F
---------	---	---	---	---	---	---	---

