

Eco Linear Double Ended R7s

DE 118MM ECO 240V 120W R7S SV1

0021714



Product features

-



PRODUCT OVERVIEW

Lamp finish	clear
Lamp shape	Linear Double Ended
Colour temperature (K)	2950
CRI (Ra)	100
Dimmable	Yes
EAN code	5410288217147
Energy class	D
Cap/Base	R7s
Beam angle(°)	na
Type	Eco Linear Double Ended R7s
Watt (Nominal) (W)	120
Light colour	829 Warm white
Ordering number	0021714
Average life (h) - L70/B50	2000
Luminous flux (Rated) (lm)	2250
Technology	Halogen
Voltage (V)	240

DATA TABLE

General data

Average life (h) at Ta 25° C	2000
Control gear required	No
Lamp finish	clear
Lamp shape	Linear Double Ended
Dimmable	Yes
EAN code	5410288217147
Energy class	D
Energy saving lamp	No
Fixture rating	Enclosed

Eco Linear Double Ended R7s

DE 118MM ECO 240V 120W R7S SV1

0021714

General application	Retail; Hospitality; Museums; Consumer; Residential;
IEC Reference	IEC 60357
IEC Reference 2	IEC 60432-3
Intended purpose	General lighting
Cap/Base	R7s
Lamp mercury content (mg)	0
Type	Eco Linear Double Ended R7s
No. of switching cycles before premature failure (min)	8000
Optimal operating condition (°C)	25
Ordering number	0021714
Product name	DE 118MM ECO 240V 120W R7S SV1
Average life (h) - L70/B50	2000
Special purpose lamp	No
Starting time (max) (s)	0.01
Technology	Halogen
Transformer required	No
Warm-up time to 60% of full light (max) (s)	Instant full light
E-number SE	8355618
E-number FI	4740101

Optical data

Colour temperature (K)	2950
CRI (Ra)	100
Beam angle(°)	na
Light colour	829 Warm white
Lumen maintenance at end of nominal life (%)	80
Luminous flux (Nominal) (lm)	2250
Luminous flux (Rated) (lm)	2250

Electrical data

kWh per 1000 hours burning time	120
Lamp power factor	1
Watt (Nominal) (W)	120
Watt (Rated) (W)	120
Voltage (V)	240

Eco Linear Double Ended R7s

DE 118MM ECO 240V 120W R7S SV1

0021714

Physical data

Max. Lamp Diameter (mm) - D	12
Lamp Length (mm) - C/L	120

TECHNICAL DRAWINGS

