

Name	SC-Focusline L
Properties	Digital 75 Ω
Properties	OFC oxygen free copper
Properties	Analog
Application area	Mobile outdoor / indoor
Application area	ELA 100 V
Application area	Installation
Application area	Studio / Broadcast
Application	video cable
Colour	black
Colour detailed	black
Construction	02YS(ST)CH0,6/3,7
Jacket material	PVC
Jacket Ø [mm]	6,20
Number of Channels (video)	1
Inner conductor (video)	1
Inner conductor (video) [mm²]	0,22
Inner conductor Ø (video) [mm]	0,60
AWG (video)	23
Shielding	Copper braiding
Copper strands (video)	7
Copper strand Ø (video) [mm]	0,20
Conductor insulation material	PE
Conductor insulation Ø [mm]	3,70
Weight per 1 m [g]	44
UV-resistant	yes
Fire load per m [kWh]	0,23
Style variant	round
Shielding factor [%]	92
Packing	100 m spool
Packing	1000 m spool
Velocity factor	0,66
Temperature min. [°C]	-20
Temperature max. [°C]	70
Width [mm]	6,2
Height [mm]	6,2
Capacity wire/electic screen at 1m (video) [pF]	67
Capacity wire/electic screen at 1 ft. (video) [pF]	20,4216
Damping at 5 MHz (100m & 20° C) [dB]	2,5
Damping at 5 MHz (100 ft. & 20 °C / 68 °F) [dB]	0,762
Damping at 50 MHz (100m & 20° C) [dB]	6,2
Damping at 50 MHz (100 ft. & 20 °C / 68 °F) [dB]	1,8898
Damping at 100 MHz (100m & 20° C) [dB]	10,2
Damping at 100 MHz (100 ft. & 20 °C / 68 °F) [dB]	3,109
Damping at 200 MHz (100m & 20° C) [dB]	13,1
Damping at 200 MHz (100 ft. & 20 °C / 68 °F) [dB]	3,9929
Impedance [Ω]	75
Conductor resistance per 1 km [Ω]	150
Conductor resistance per 1000 ft. [Ω]	45,72
Shield. resistance per 1 km [Ω]	13
Shield. resistance per 1000 ft. [Ω]	3,9624
EAN	4049371004046