



MASTER TL-D 90 De Luxe

MASTER TL-D 90 De Luxe 36W/940 SLV/10

This TL-D lamp makes colors appear rich, deep and enhanced in a natural way. Thus very suitable for applications where a high color recognition is needed: first aid and treatment rooms in hospitals, printing rooms, jewelry, dentists, hairdressing, museums and shops

Product data

| General Information | |
|------------------------------------|----------------------------------|
| Cap-Base | G13 [Medium Bi-Pin Fluorescent] |
| Bulb Shape | T8 [26 mm (T8)] |
| Life To 10% Failures (Nom) | 12000 h |
| Life To 50% Failures (Nom) | 15000 h |
| Life To 50% Failures Preheat (Nom) | 20000 h |
| LSF 2000 h Rated | 99 % |
| LSF 4000 h Rated | 99 % |
| LSF 6000 h Rated | 99 % |
| LSF 8000 h Rated | 99 % |
| LSF 12000 h Rated | 89 % |
| LSF 16000 h Rated | 33 % |
| LSF 20000 h Rated | 2 % |
| | |
| Light Technical | |
| Color Code | 940 [CCT of 4000K] |
| Luminous Flux (Nom) | 2800 lm |
| Luminous Flux (Rated) (Nom) | 2800 lm |
| Color Designation | Cool White (CW) |
| Chromaticity Coordinate X (Nom) | 381 |
| · | |

| Chromaticity Coordinate Y (Nom) | 379 |
|------------------------------------|-----------|
| Correlated Color Temperature (Nom) | 4000 K |
| Luminous Efficacy (rated) (Nom) | 77.8 lm/W |
| Color Rendering Index (Nom) | 91 |
| LLMF 2000 h Rated | 96 % |
| LLMF 4000 h Rated | 95 % |
| LLMF 6000 h Rated | 94 % |
| LLMF 8000 h Rated | 93 % |
| LLMF 12000 h Rated | 92 % |
| LLMF 16000 h Rated | 91 % |
| LLMF 20000 h Rated | 90 % |
| | · |
| Operating and Electrical | · |
| Power (Rated) (Nom) | 36.0 W |
| Lamp Current (Nom) | 0.440 A |
| | |
| Temperature | |
| Design Temperature (Nom) | 25 °C |
| | |
| | |


Datasheet, 2016, December 27 data subject to change

MASTER TL-D 90 De Luxe

| Controls and Dimming | | |
|-------------------------------|-----------------|--|
| Dimmable | Yes | |
| Approval and Application | | |
| Energy Efficiency Label (EEL) | A | |
| Mercury (Hg) Content (Nom) | 2 mg | |
| Energy Consumption kWh/1000 h | 43 kWh | |
| Product Data | | |
| Full product code | 871150088858725 | |

| Order product name | MASTER TL-D 90 De Luxe 36W/940 SLV/10 |
|---------------------------------|---------------------------------------|
| EAN/UPC - Product | 8711500888587 |
| Order code | 928044594081 |
| Numerator - Quantity Per Pack | 1 |
| Numerator - Packs per outer box | 10 |
| Material Nr. (12NC) | 928044594081 |
| Net Weight (Piece) | 137.500 g |
| ILCOS Code | FD-36/38/1A-E-G13 |
| | |

Dimensional drawing



TL-D De Luxe 36W/940





Product