

<b>Name</b>	Elephant SPM425
<b>Properties</b>	OFC oxygen free copper
<b>Properties</b>	Analog
<b>Application area</b>	Stage / live
<b>Application area</b>	Installation
<b>Application area</b>	Studio / Broadcast
<b>Application area</b>	Mobile outdoor / indoor
<b>Application area</b>	ELA 100 V
<b>Application</b>	Speaker Cable
<b>Colour</b>	black
<b>Colour detailed</b>	black
<b>Construction</b>	(4LIY2,5mm <sup>2</sup> )Y
<b>Jacket material</b>	PVC
<b>Jacket Ø [mm]</b>	10,20
<b>Number of Channels (audio)</b>	1
<b>Inner conductor (audio)</b>	4
<b>Inner conductor (audio) [mm<sup>2</sup>]</b>	2,50
<b>Inner conductor Ø (audio) [mm]</b>	1,78
<b>AWG (audio)</b>	13
<b>Copper strands (audio)</b>	78
<b>Copper strand Ø (audio) [mm]</b>	0,20
<b>Conductor insulation Ø [mm]</b>	3,05
<b>Weight per 1 m [g]</b>	180
<b>UV-resistant</b>	yes
<b>Fire load per m [kWh]</b>	0,8
<b>Style variant</b>	round
<b>Packing</b>	bulk stock
<b>Temperature min. [°C]</b>	-25
<b>Temperature max. [°C]</b>	70
<b>Width [mm]</b>	10,2
<b>Height [mm]</b>	10,2
<b>Insulation resist. per 1 km [GΩ]</b>	0,005
<b>Insulation resist. per 1000 feet [GΩ]</b>	0,0015
<b>Insulation resist. per 1 km (audio) [GΩ]</b>	0,005
<b>Insulation resist. per 1000 feet (audio) [GΩ]</b>	0,0015
<b>Conductor resistance per 1 km [Ω]</b>	7,7
<b>Conductor resistance per 1000 ft. [Ω]</b>	2,347
<b>Test voltage [V]</b>	2000
<b>EAN</b>	4049371002233