

Name	SC-Stratos, Longlife
Properties	OFC oxygen free copper
Properties	Analog
Application area	Studio / Broadcast
Application area	Installation
Application	Hifi- & Instrumen cable, HighEnd
Colour	grey
Colour detailed	anthracite
Signal transmission	asymmetrical
Construction	(LIHS09YHS1x0,34mm²)DY
Jacket material	PVC
Jacket Ø [mm]	8,50
Number of Channels (audio)	1
Inner conductor (audio)	1
Inner conductor (audio) [mm²]	0,34
Inner conductor Ø (audio) [mm]	0,66
AWG (audio)	22
Shielding	Copper braided shielding + semiconductor
Copper strands (audio)	7
Copper strand Ø (audio) [mm]	0,25
Conductor insulation material	PE / PP
Weight per 1 m [g]	74
Fire load per m [kWh]	0,25
Style variant	round
Shielding factor [%]	100
Packing	bulk stock
Temperature min. [°C]	-20
Temperature max. [°C]	80
Width [mm]	8,5
Height [mm]	8,5
Capac. cond./shield. per 1 m (audio) [pF]	75
Capacity wire/electic screen at 1 ft. (audio) [pF]	22,86
Insulation resist. per 1 km [GΩ]	1
Insulation resist. per 1000 feet [GΩ]	0,3048
Insulation resist. per 1 km (audio) [GΩ]	1
Insulation resist. per 1000 feet (audio) [GΩ]	0,3048
Conductor resistance per 1 km [Ω]	53
Conductor resistance per 1000 ft. [Ω]	16,1544
EAN	4049371003209