

RIGLINK COMBO CABLES

FEATURES

- Power and data all through one cable.
- Ideal for both installations and touring.
- IP65 rated for outdoor use.
- Individually insulated for minimal interference.

RIGLINK CABLES

- Color-coded connectors eliminate cable length guesswork
- Certified components meet worldwide safety standards
- Built rugged for live performance and life on the road
- Reliable transmission and robust connection systems
- Seetronic® professional production grade connectors
- Cable lengths available in both meters and feet



SPECIFICATIONS

CONSTRUCTION / PHYSICAL

- Conductor Specification: 2 x 0.34mm² (22AWG) & 3 x 2.07mm² (14AWG)
- Conductor Structure: OFC 19/0.15TC & 66/0.20BC
- Insulation Material: HDPE & PVC
- Insulation OD: 1.4mm & 3.0mm
- Filler: Cotton & PPR
- Wrapping Tape: Non-woven fabric
- Shield Structure: Tinned copper wire, 82% AL, 100% coverage
- Middle Quilt: PVC
- Outer Jacket Material: PVC (Black)
- Outer Diameter: 16.5 ± 0.2mm
- Temperature Rating: -20°C – 70°C
- IP65

CONNECTIONS

- Seetronic SAC3FX
- Seetronic SCWM5-B
- Seetronic SAC3MX
- Seetronic SCWF5-B

ELECTRICAL

- Withstand Voltage: 0.5/1.5 AC kV/min
- Conductor Resistance: 25.98 /km & 7.98 /km
- Capacitance between Connectors: 100pF/m
- Conductor shields capacitance: 180pF/m
- Impedance: 110

CABLE

- Metric: 1m, 3m, 5m, 10m
- Imperial: 1.5ft, 5ft, 10ft, 25ft

Length	SKU	Description
1.5FT	RIGLINKCOMBO15FT	1.5 ft TR1 DMX Combo Cable
1M	RIGLINKCOMBO1M	1 m TR1 DMX Combo Cable
5FT	RIGLINKCOMBO5FT	5 ft TR1 DMX Combo Cable
3M	RIGLINKCOMBO3M	3 m TR1 DMX Combo Cable
10FT	RIGLINKCOMBO10FT	10 ft TR1 DMX Combo Cable
5M	RIGLINKCOMBO5M	5 m TR1 DMX Combo Cable
25FT	RIGLINKCOMBO25FT	25 ft TR1 DMX Combo Cable
10M	RIGLINKCOMBO10M	10 m TR1 DMX Combo Cable

RIGLINK

Riglink is CHAUVET Professional's new line of DMX, IP65, Powerkon, 3-pin, and 4-pin cables.