

Name	Elephant SPM825
Properties	OFC oxygen free copper
Properties	Analog
Application area	Stage / live
Application area	Installation
Application area	Studio / Broadcast
Application area	Mobile outdoor / indoor
Application area	ELA 100 V
Application	Speaker Cable
Colour	black
Colour detailed	black
Construction	(8LIY2,5mm²)Y
Jacket material	PVC
Jacket Ø [mm]	15,30
Number of Channels (audio)	1
Inner conductor (audio)	8
Inner conductor (audio) [mm²]	2,50
Inner conductor Ø (audio) [mm]	1,78
AWG (audio)	13
Copper strands (audio)	78
Copper strand Ø (audio) [mm]	0,20
Conductor insulation Ø [mm]	3,25
Weight per 1 m [g]	354
UV-resistant	yes
Fire load per m [kWh]	1,9
Style variant	round
Packing	bulk stock
Temperature min. [°C]	-25
Temperature max. [°C]	70
Width [mm]	15,3
Height [mm]	15,3
Insulation resist. per 1 km [GΩ]	0,005
Insulation resist. per 1000 feet [GΩ]	0,0015
Insulation resist. per 1 km (audio) [GΩ]	0,005
Insulation resist. per 1000 feet (audio) [GΩ]	0,0015
Conductor resistance per 1 km [Ω]	7,6
Conductor resistance per 1000 ft. [Ω]	2,3165
Test voltage [V]	2000
EAN	4049371020503