

Name	Elephant SPM4025
Properties	Analog
Properties	OFC oxygen free copper
Properties	PUR
Application area	Mobile outdoor / indoor
Application area	ELA 100 V
Application area	Stage / live
Application area	Installation
Application area	Studio / Broadcast
Application	Speaker Cable
Colour	black
Colour detailed	black
Construction	(2LIY2,5 mm² + 4LIY4,0 mm²)Y
Jacket material	PVC
Jacket Ø [mm]	14,80
Number of Channels (audio)	1
Inner conductor (audio)	4
Inner conductor (audio)	2
Inner conductor (audio) [mm²]	4,00
Inner conductor (audio) [mm²]	2,50
AWG (audio)	11
AWG (audio)	13
Copper strands (audio)	84
Copper strands (audio)	82
Copper strand Ø (audio) [mm]	0,19
Copper strand Ø (audio) [mm]	0,25
Conductor insulation Ø [mm]	3,75
Conductor insulation Ø [mm]	3,05
Weight per 1 m [g]	380
UV-resistant	yes
Fire load per m [kWh]	0,76
Style variant	round
Packing	bulk stock
Temperature min. [°C]	-25
Temperature max. [°C]	70
Width [mm]	14,8
Height [mm]	14,8
Insulation resist. per 1 km [GΩ]	0,005
Insulation resist. per 1000 feet [GΩ]	0,0015
Insulation resist. per 1 km (audio) [GΩ]	0,005
Insulation resist. per 1000 feet (audio) [GΩ]	0,0015
Conductor resistance per 1 km [Ω]	7,5
Conductor resistance per 1000 ft. [Ω]	2,286
Test voltage [V]	2000
EAN	4049371005388