

Name	Elephant Robust SPM1640
Properties	OFC oxygen free copper
Properties	Analog
Application area	Stage / live
Application area	Installation
Application area	Studio / Broadcast
Application area	Mobile outdoor / indoor
Application area	ELA 100 V
Application	Speaker Cable
Colour	black
Colour detailed	black
Construction	(16LIY4,0mm²)Y
Jacket material	PVC
Jacket Ø [mm]	20,50
Number of Channels (audio)	1
Inner conductor (audio)	16
Inner conductor (audio) [mm²]	4,00
Inner conductor Ø (audio) [mm]	2,26
AWG (audio)	11
Copper strands (audio)	128
Copper strand Ø (audio) [mm]	0,20
Conductor insulation Ø [mm]	3,65
Weight per 1 m [g]	932
UV-resistant	yes
Fire load per m [kWh]	2,7
Style variant	round
Packing	bulk stock
Temperature min. [°C]	-25
Temperature max. [°C]	70
Width [mm]	20,5
Height [mm]	20,5
Insulation resist. per 1 km [GΩ]	0,005
Insulation resist. per 1000 feet [GΩ]	0,0015
Insulation resist. per 1 km (audio) [GΩ]	0,005
Insulation resist. per 1000 feet (audio) [GΩ]	0,0015
Conductor resistance per 1 km [Ω]	4,5
Conductor resistance per 1000 ft. [Ω]	1,3716
Test voltage [V]	2000
EAN	4049371005371