

|                                                     |                                                      |
|-----------------------------------------------------|------------------------------------------------------|
| Name                                                | SC-Primus                                            |
| Properties                                          | Analog                                               |
| Properties                                          | OFC oxygen free copper                               |
| Application area                                    | Studio / Broadcast                                   |
| Application area                                    | Mobile outdoor / indoor                              |
| Application area                                    | ELA 100 V                                            |
| Application area                                    | Stage / live                                         |
| Application area                                    | Installation                                         |
| Application                                         | Microphone Cable                                     |
| Colour                                              | black                                                |
| Colour detailed                                     | black                                                |
| Signal transmission                                 | symmetrical                                          |
| Construction                                        | (2LI2Y0,50mm²)(ST)DY                                 |
| Jacket material                                     | PVC                                                  |
| Jacket Ø [mm]                                       | 6,50                                                 |
| Number of Channels (audio)                          | 1                                                    |
| Inner conductor (audio)                             | 2                                                    |
| Inner conductor (audio) [mm²]                       | 0,50                                                 |
| Inner conductor Ø (audio) [mm]                      | 0,80                                                 |
| AWG (audio)                                         | 20                                                   |
| Shielding                                           | Copper spiral sleeve tin-plated +<br>metallic fleece |
| Copper strands (audio)                              | 28                                                   |
| Copper strand Ø (audio) [mm]                        | 0,15                                                 |
| Conductor insulation material                       | PE                                                   |
| Conductor insulation Ø [mm]                         | 1,65                                                 |
| Weight per 1 m [g]                                  | 53,97                                                |
| UV-resistant                                        | yes                                                  |
| Fire load per m [kWh]                               | 0,23                                                 |
| Style variant                                       | round                                                |
| Shielding factor [%]                                | 100                                                  |
| Packing                                             | 100 m spool                                          |
| Packing                                             | 500 m spool                                          |
| Temperature min. [°C]                               | -25                                                  |
| Temperature max. [°C]                               | 70                                                   |
| Width [mm]                                          | 6,5                                                  |
| Height [mm]                                         | 6,5                                                  |
| Capac. cond./cond. per 1 m (audio) [pF]             | 80                                                   |
| Capacity wire/wire at 1 ft. (audio) [pF]            | 24,384                                               |
| Capac. cond./shield. per 1 m (audio) [pF]           | 145                                                  |
| Capacity wire/electric screen at 1 ft. (audio) [pF] | 44,196                                               |
| Insulation resist. per 1 km [GΩ]                    | 1                                                    |
| Insulation resist. per 1000 feet [GΩ]               | 0,3048                                               |
| Insulation resist. per 1 km (audio) [GΩ]            | 1                                                    |
| Insulation resist. per 1000 feet (audio) [GΩ]       | 0,3048                                               |
| Conductor resistance per 1 km [Ω]                   | 37                                                   |
| Conductor resistance per 1000 ft. [Ω]               | 11,2776                                              |
| Shield. resistance per 1 km [Ω]                     | 27                                                   |
| Shield. resistance per 1000 ft. [Ω]                 | 8,2296                                               |
| EAN                                                 | 4049371001960                                        |