

Name	Tricone® MKII
Properties	OFC oxygen free copper
Properties	Analog
Application area	Installation
Application area	Mobile outdoor / indoor
Application area	Stage / live
Application	Instrument Cable
Colour	black
Colour detailed	black
Signal transmission	asymmetrical
Construction	LI2Y(LS)DY1x0,22mm²
Jacket material	PVC
Jacket Ø [mm]	5,90
Number of Channels (audio)	1
Inner conductor (audio)	1
Inner conductor (audio) [mm²]	0,22
Inner conductor Ø (audio) [mm]	0,53
AWG (audio)	24
Shielding	Copper braided shielding + semiconductor
Copper strands (audio)	28
Copper strand Ø (audio) [mm]	0,10
Conductor insulation material	Foam / Skin-PE
Conductor insulation Ø [mm]	1,80
Weight per 1 m [g]	42
UV-resistant	yes
Fire load per m [kWh]	0,26
Style variant	round
Shielding factor [%]	100
Packing	500 m spool
Packing	100 m spool
Temperature min. [°C]	-25
Temperature max. [°C]	60
Width [mm]	5,9
Height [mm]	5,9
Capac. cond./shield. per 1 m (audio) [pF]	85
Capacity wire/electic screen at 1 ft. (audio) [pF]	25,908
Insulation resist. per 1 km [GΩ]	1
Insulation resist. per 1000 feet [GΩ]	0,3048
Insulation resist. per 1 km (audio) [GΩ]	1
Insulation resist. per 1000 feet (audio) [GΩ]	0,3048
Conductor resistance per 1 km [Ω]	90
Conductor resistance per 1000 ft. [Ω]	27,432
EAN	4049371002134