



MSR

MSR 1200 1CT/3


The high color rendering index of the single ended MSR series ensures that everyone in the audience can enjoy the true colors of the scenery, the stage props, the players and their costumes – in fact everything that is on stage can be made bright and vivid in daylight quality light. Also, thanks to the single ended lamp concept, the luminaire has optimal light collection and direction possibilities to help ensure brightness on stage exactly where and when it is needed. In addition, the MSR can be used in any burning position for easy set-up and convenience.

Product data

General Information		Lamp Current (Nom)		13.8 A
Cap-Base	G22 [G22]	Ignition Supply Voltage (Min)		207 V
Operating Position	UNIVERSAL [Any or Universal (U)]	Controls and Dimming		
Main Application	Studio/Disco	Dimmable		No
Life To 50% Failures (Nom)	800 h	Mechanical and Housing		
System Description	Cold Strike	Cap-Base Information		30 mm x 53 mm
Light Technical		Luminaire Design Requirements		
Color Code	- [Not Specified]	Bulb Temperature (Max)		700 °C
Luminous Flux (Min)	94000 lm	Pinch Temperature (Max)		350 °C
Luminous Flux (Nom)	110000 lm	Product Data		
Chromaticity Coordinate X (Nom)	325	Full product code		872790091121300
Chromaticity Coordinate Y (Nom)	320	Order product name		MSR 1200 1CT/3
Correlated Color Temperature (Nom)	5900 K	EAN/UPC - Product		8727900911213
Luminous Efficacy (rated) (Nom)	91 lm/W	Order code		928078105114
Color Rendering Index (Nom)	80	Numerator - Quantity Per Pack		1
Operating and Electrical				
Power (Rated) (Nom)	1200 W			

Numerator - Packs per outer box	3
Material Nr. (12NC)	928078105114
Net Weight (Piece)	0.150 kg

Dimensional drawing



MSR 1200

Product	D	O	L	L	L	C	F
---------	---	---	---	---	---	---	---

