



article#	313-4f5v
article description	CEE-flanged socket straight (55x55mm) 16A 3p 4h IP44/IP54
description long	CEE-flanged socket straight (55x55mm) 16A 3p 4h IP44/IP54 housing material: PA6 rated current: 16A number of poles: 3 (2P+PE) clock-position: 4h rated voltage/frequency: 100-130V~ / 50+60Hz contacts: brass nickel plated connection technology: screw terminals dimensions (flange/fixing center): 55x55 mm / 44x44 mm IP protection class: IP44/IP54
GTIN (EAN)	9003399043376
country of origin	AT
customs number	85366990
net weight	0.102 kg
packaging quantity	10
minimum order quantity	10

ETIM 9.0	EC001317
IEC-ampereage	16 A
Voltage according to EN 60309-2	110 V (50+60 Hz) yellow
Number of poles	3
Clock hour position	4 h
Identification colour	Yellow
Degree of protection (IP)	IP54
Connection system	Screwed terminal
Angle of plug	Straight
Material	Plastic
Contact material	CuZn
Surface treatment contacts	Nickel-plated
Flange size vertical	55 mm
Drill hole distance vertical	44 mm
Flange size horizontal	55 mm
Drill hole distance horizontal	44 mm

a	55 mm
b	55 mm
c	44 mm
d	44 mm
e	21 mm
f	55 mm
g	5,5 mm
h	43 mm
i	80 mm
j	101 mm
wire flexible	1-2,5 mm ²
wire solid	1-4 mm ²
contact screws	100 Ncm
dismantling length	50 mm
stripping length	10-12 mm
ambient temperature	-25 – 40 °C
temperature resistance	-25 – 80 °C



<https://www.pcelectric.at/shop/en/?func=detail&artnr=313-4f5v>

