




GE
Lighting



693
kWh/1000h

D
energy class

0
lumens/watt

PAR 36

DWE Q650PAR36/1 120V

41667

Product information

PAR lamps provide a robust and flexible design solution for a wide range of applications. Choice of PAR36, PAR46, PAR56 or PAR64

- 3000 K or 4200 K colour temperature
- Choice of beam widths
- Excellent colour rendering
- High efficiency combined with low operating costs
- Robust and reliable
- UV control
- Easy retrofit
- Colour consistent throughout life
- Colour blends with halogen and fluorescent

Application areas



Club and Disco



WORLDWIDE PARTNER

Product data

Product Code	41667
Bulb Shape	PAR
Bulb Finish	Aluminized
Bulb Diameter [mm]	114.3
Maximum Overall Length [mm]	70
Net weight per piece [g]	230
Gross weight per piece [g]	255
Brand	General Electric (GE)
Cap/Base	Screw terminal

Performance data

Nominal beam angle [°]	21
Nominal center beam candlepower (CBCP) [cd]	24000
Weighted energy consumption [kWh/1000h]	692.4
Energy efficiency class (EEC)	D
Rated Life [h]	100
Nominal correlated colour temperature (CCT) [K]	3200
Nominal lumens [lm]	1

Electrical data

Coil type	CC-6
Ballast Required	Yes
Nominal power [W]	650
Nominal lamp voltage [V]	120

Logistic data

DUN Code	00043168416672
EAN Code	0043168416672
Pack Quantity	12
Layer quantity	1 UK
Layer quantity UK	1
Pallet quantity UK (PC)	1200
Outer case size	226 x 211 x 313 (mm)
Product status	Available

Downloads & Links

[Go to the catalog site \(HTTP\)](#)

[High-res images / Technical drawings \(HTTP\)](#)

[Certificate for the Quality Management System of GE Lighting EMEA \(PDF\)](#)

[Certificate for the Environmental Management System of GE Lighting EMEA \(PDF\)](#)

Disclaimer

Special purpose lamp – Stage Studio. Not suitable for household illumination.