







Single Ended Halogen - HPL HPL 575W 240V

88477

Product information

HPL lamps were developed using GE Six Sigma process, these lamps encompass modern halogen technology and high production standards. HPL optical system for superior field smoothness and cosine distribution—Integral heat sink base reduces seal temperature, increases durability and maximises life—Shock resistant filament array and patented gas chemistry minimises arc-out risk during alignment and focusing.

Application areas











Product data

Product Code	88477
Bulb Shape	Tubular
Bulb Diameter [mm]	19
Maximum Overall Length [mm]	106
Light Center Length [mm]	60.3
Net weight per piece [g]	54
Gross weight per piece [g]	73
Brand	General Electric (GE)
Cap/Base	G9.5

Performance data

Weighted energy consumption [kWh/1000h]	597.77
Energy efficiency class (EEC)	D
Rated Life [h]	300
Nominal correlated colour temperature (CCT) [K]]	3200
Nominal lumens [lm]	14900
Colour Rendering Index (CRI) [Ra]	100

Electrical data

Coil type	6C-8
Ballast Required	No
Nominal power [W]	575
Nominal lamp voltage [V]	240



Logistic data

10043168884775
0043168884778
12
468 EUR, 588 UK
468
588
3276
4116
175 x 135 x 138 (mm)
Available

Downloads & Links

Go to the catalog site (HTTP)

Entertainment Solution Spectrum Catalogue (PDF)

Lighting design tools & calculators (HTTP)

High-res images / Technical drawings (HTTP)

Certificate for the Quality Management System of GE Lighting EMEA (PDF)

Certificate for the Environmental Management System of GE Lighting EMEA (PDF)

Disclaimer

Special Purpose Lamp, Not suited for household illumination