

Black Microphone Cable

Item Code: 1E00209

CVS LK02N6E

GENERAL DATA

Application	Mobile
Cable O.D. (mm)	6
Min Operating Temperature (°C)	-20
Max Operating Temperature (°C)	70
Standard Reels (m)	100
Reel Material	Cardboard
Weight (Kg/100m)	4.60
Jacket Color	Black
Jacket Material	Extra-flexible PVC
Jacket Nominal Thickness (mm)	1.5

ELECTRICAL DATA

Max Conductor DCR [Audio] (ohm/km)	78
Conductor/Conductor Capacitance (pF/m)	75
Conductor/Shield Capacitance (pF/m)	150
Nominal Impedance (ohm/100m)	1
Attenuation @ 1 KHz (dB/100m)	2
Max Inductance (μH/100m)	3

CONDUCTOR

Conductors Quantity	2
Conductor Strands	30
Conductor Strands O.D. (mm)	0.1
Conductor Area (mm ²)	0.22
Conductor AWG	24
Conductor Material	Flexible electrolytic bare copper
Conductor Insulation O.D. (mm)	1.1

SHIELD

Shield Material	Spiraled electrolytic bare copper
Shield Coverage	70%

ADDITIONAL INFORMATION

Notes	Not suitable for applications above 50 volt ac; 75 volt dc.
-------	---