

Name	SC-Galileo 238 Plus
Properties	Analog
Properties	OFC oxygen free copper
Application area	Mobile outdoor / indoor
Application area	Stage / live
Application area	Installation
Application area	Studio / Broadcast
Application	Microphone Cable
Colour	black
Colour detailed	black
Signal transmission	symmetrical
Construction	(2LI2Y0,38mm²)YDDY
Jacket material	PVC
Jacket Ø [mm]	7,00
Number of Channels (audio)	1
Inner conductor (audio)	2
Inner conductor (audio) [mm²]	0,38
Inner conductor Ø (audio) [mm]	0,70
AWG (audio)	21
Shielding	Double copper spiral, counter-rotating + polyester tape
Copper strands (audio)	48
Copper strand Ø (audio) [mm]	0,10
Conductor insulation material	PE
Conductor insulation Ø [mm]	1,55
Weight per 1 m [g]	60
UV-resistant	yes
Fire load per m [kWh]	0,22
Style variant	round
Shielding factor [%]	100
Packing	100 m spool
Temperature min. [°C]	-30
Temperature max. [°C]	70
Width [mm]	7
Height [mm]	7
Capac. cond./cond. per 1 m (audio) [pF]	50
Capacity wire/wire at 1 ft. (audio) [pF]	15,24
Capac. cond./shield. per 1 m (audio) [pF]	100
Capacity wire/electic screen at 1 ft. (audio) [pF]	30,48
Impedance [Ω]	38
Insulation resist. per 1 km [GΩ]	1
Insulation resist. per 1000 feet [GΩ]	0,3048
Insulation resist. per 1 km (audio) [GΩ]	1
Insulation resist. per 1000 feet (audio) [GΩ]	0,3048
Conductor resistance per 1 km [Ω]	52
Conductor resistance per 1000 ft. [Ω]	15,8496
Shield. resistance per 1 km [Ω]	20
Shield. resistance per 1000 ft. [Ω]	6,096
EAN	4049371001229