

64716 600 W 230 V

Halogen (> 130 V) Single End




Areas of application

- Stage & Theatre
- Studio, TV, & Film
- Professional Photography
- Club & Disco

Product features and benefits

- Robust construction for lasting performance
- Consistent color over the life of the lamps
- Instant on and nearly constant luminous flux over the life of the lamp
- Broad product portfolio supporting the stage and studio markets
- Dimmable with traditional amber shift



Technical data

General Product Information

Product number (Americas)	54493
Product name (Americas)	64716 GKV 600W 230V 12/CS 1/SKU
Lamp type	SINGLE END
ANSI code	GKV
LIF code	-
Global order reference	64716


Electrical Data

Nominal wattage	600 W
Nominal voltage	230 V
Type of current	AC

Photometric Data

Nominal luminous flux	13500 lm
Useful luminous flux (Φ_{use})	14210 lm
Φ_{use} value refers to luminous flux	360
Luminous efficacy	22.4 lm/W
Illuminated field	9.0*13.0 mm ²
Color temperature	3050 K
Correlated color temperature CCT	3118 K
Chromaticity coordinate x	0.429
Chromaticity coordinate y	0.401
Color rendering index Ra	100
Light center length (LCL)	60.5 mm
Light center length (LCL) - (in)	2.38 in

Physical Attributes & Dimensions



Lamp base	G9.5
Diameter (in)	0.720 in
Diameter	19.0 mm
Length	101.0 mm
Product weight	28.00 g

Operating Conditions

Burning position	s90
Dimmable	Yes
Cooling	Convection

Lifetime Data

Nominal lifetime	300 hr
------------------	--------

Environmental & Regulatory Information

Information according Art. 33 of EU Regulation (EC) 1907/2006 (REACH)	
Primary article identifier	4008321623973
Energy efficiency class	G
Declaration no. in SCIP database	No declarable substances contained
Candidate list substance 1	No declarable substances contained

Product datasheet

Safety advice

To prevent personal injury or damage to property, halogen lamps may only be operated in suitable luminaires designed with suitable mechanisms (protective shields, grids, etc.) to ensure that in the event of a lamp bursting no parts/shards can escape and that during operation no ultraviolet radiation can escape. There must also be a warning sign to indicate that the lamps give off high levels of heat. Detailed information is available on request.

Logistical Data

Product code	Product description	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Volume	Gross weight
4008321623973	64716 600 W 230 V	Folding carton box 1	40 mm x 40 mm x 128 mm	0.21 dm ³	51.00 g
4008321623980	64716 600 W 230 V	Shipping carton box 12	177 mm x 136 mm x 152 mm	3.70 dm ³	812.00 g

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.
