

Name	SC-Onyx Tynee
Properties	Analog
Properties	OFC oxygen free copper
Application area	Installation
Application area	Studio / Broadcast
Application	Patch & Instrument Cable
Colour	black
Colour detailed	black
Signal transmission	asymmetrical
Construction	LI2YDY1x0,22mm2
Jacket material	PVC
Jacket Ø [mm]	4,00
Number of Channels (audio)	1
Inner conductor (audio)	1
Inner conductor (audio) [mm²]	0,22
Inner conductor Ø (audio) [mm]	0,53
AWG (audio)	24
Shielding	Copper spiral shielding
Copper strands (audio)	7
Copper strand Ø (audio) [mm]	0,20
Conductor insulation material	PE
Weight per 1 m [g]	18
UV-resistant	yes
Fire load per m [kWh]	0,12
Style variant	round
Shielding factor [%]	95
Packing	100 m spool
Temperature min. [°C]	-20
Temperature max. [°C]	70
Width [mm]	4
Height [mm]	4
Capac. cond./shield. per 1 m (audio) [pF]	125
Capacity wire/electric screen at 1 ft. (audio) [pF]	38,1
Insulation resist. per 1 km [GΩ]	1
Insulation resist. per 1000 feet [GΩ]	0,3048
Insulation resist. per 1 km (audio) [GΩ]	1
Insulation resist. per 1000 feet (audio) [GΩ]	0,3048
Conductor resistance per 1 km [Ω]	85
Conductor resistance per 1000 ft. [Ω]	25,908
EAN	4049371002080