



# CDM-SA/T

## CDM-SA/T 150W/942 1CT/12

With a high luminous efficacy producing more lumens per watt than standard Architectural lamps, the CDM-SA/T is the greener alternative to light up the night. In addition, the optimal lamp filling and short arc of the lamp create a high beam intensity and excellent color rendering.


### Product data

General Information	
Cap-Base	G12 [ G12]
Operating Position	UNIVERSAL [ Any or Universal (U)]
Main Application	Dynamic Architectural
Life To 50% Failures (Nom)	9000 h
Light Technical	
Color Code	942 [ CCT of 4200K]
Luminous Flux (Min)	12600 lm
Luminous Flux (Nom)	14000 lm
Color Designation	Cool White (CW)
Chromaticity Coordinate X (Nom)	380
Chromaticity Coordinate Y (Nom)	360
Correlated Color Temperature (Nom)	4200 K
Luminous Efficacy (rated) (Nom)	91 lm/W
Color Rendering Index (Nom)	95
Operating and Electrical	
Power (Rated) (Nom)	150 W
Lamp Current (Nom)	1.8 A
Ignition Supply Voltage (Min)	198 V

Controls and Dimming	
Dimmable	No
Approval and Application	
Mercury (Hg) Content (Max)	11.9 mg
Luminaire Design Requirements	
Bulb Temperature (Max)	650 °C
Pinch Temperature (Max)	350 °C
Product Data	
Full product code	871150020094515
Order product name	CDM-SA/T 150W/942 1CT/12
EAN/UPC - Product	8711500200945
Order code	928086605103
Numerator - Quantity Per Pack	1
Numerator - Packs per outer box	12
Material Nr. (12NC)	928086605103
Net Weight (Piece)	0.030 kg

CDM-SA/T

Dimensional drawing



CDM-SA/T 150W/942

Product	D	O	L	L	L	C	F	F	F
---------	---	---	---	---	---	---	---	---	---

