



# Discharge - Single Ended Hot Restrike CSR 1800/SE/HR 77390

# **Product information**

Compact, single ended metal halide hot restrike lamps for a variety of applications requiring high luminance, reliability and excellent colour characteristics. Excellent colour rendering, Ra>90, and high CCT 5600–6000 K with superior colour stability- Universal burn position with hot restrike capability- High efficiency with excellent lumen maintenance -Available with UV blocking.

#### **Application areas**



Film and Broadcast









### Product data

Product Code	77390
Bulb Shape	Tubular
Bulb Finish	Clear
Bulb Diameter [mm]	42
Maximum Overall Length [mm]	200
Light Center Length [mm]	107
Arc Gap	12
Net weight per piece [g]	285
Gross weight per piece [g]	730
Operating position	U - Universal
Brand	General Electric (GE)
Cap/Base	G38

### Performance data

Colour Code	960
Weighted energy consumption [kWh/1000h]	1980
Energy efficiency class (EEC)	A+
Nominal chromaticity coordinate X	0.333
Nominal chromaticity coordinate Y	0.333
Nominal correlated colour temperature (CCT) [K]]	6000
Nominal lumens [lm]	165000
Colour Rendering Index (CRI) [Ra]	90

## **Electrical data**

Lamp Current [A]	12
Dimming Capability	No
Ballast Required	Yes
Nominal power [W]	1800
Nominal lamp voltage [V]	150





#### Logistic data

DUN Code	10043168773901
EAN Code	0043168773904
Pack Quantity	6
Inner pack type	BOX
Layer quantity	36 EUR, 66 UK
Layer quantity EUR	36
Layer quantity UK	66
Pallet quantity EUR (PC)	108
Pallet quantity UK (PC)	132
Outer case size	385 x 280 x 346 (mm)
Product status	Available

Downloads & Links Go to the catalog site (HTTP) Entertainment Solution Spectrum Catalogue (PDF) Lighting design tools & calculators (HTTP) High-res images / Technical drawings (HTTP) Certificate for the Quality Management System of GE Lighting EMEA (PDF) Certificate for the Environmental Management System of GE Lighting EMEA (PDF)

#### Disclaimer

Special Purpose Lamp, Not suited for household illumination