DRIVENET 832 POWER







32 OUTPUT CHANNELS (INDIVIDUALLY PROGRAMMABLE) **CONTROLLED VIA RDM / DMX 512 ARTNET (OPTIONAL INTERFACE) CURRENT SELECTABLE** FOR EACH OUTPUT CHANNEL TOUCH-SCREEN COLOR DISPLAY **UPDATABLE OPERATING SYSTEM MONITORING OF PROJECTORS** STATUS ON BUILT-IN DISPLAY



DRIVENET 832 POWER is the most advanced 32-channel rack-mountable, 180-240 Vac 50-60 Hz, power supply / controller unit in DTS range. DRIVENET 832 POWER introduces a series of cutting edge features:

- * 32 output channels individually programmable (8 groups, 4 channels each).
- * Unit controlled via RDM/DMX512 protocol or Art-Net protocol (with optional interface)
- * Current individually selectable for each output channel.
- * Touch-screen color display for managing any function.
- * Updatable operating software.
- DRIVENET 832 POWER can control a vast range of DTS LED projectors.
- DRIVENET 832 POWER can also control any other current-driven LED projector matching the unit output specifications.
- DRIVENET 832 POWER is fitted with screw terminal connectors.
- *Voltage not compatible in: USA, Canada, Mexico, Venezuela, Colombia, Ecuador, Central America and Carribean area, Japan, Taiwan, Libia.





VENET 832 POWER



I OUTPUT I

Output channels: 32 (4 channels x 8 groups) Output current: up to 1600 mA (individually selectable for each output channel) Output voltage: 48 Vdc Max power: 2400 W

I DISTANCE BETWEEN DRIVENET AND PROJECTORS I

Max 50 m

I CONNECTIONS I

Output: 8-pole screw terminals connectors DMX In/Out: 2 x XLR 5-pole and XLR 3-pole chassis connectors

I INPUT VOLTAGE / FREQUENCY RANGE I

180 - 240 Vac 50-60 Hz

I CONTROL I

Protocols: RDM / DMX 512 Art-Net (optional interface required) Touch-screen color display Monitoring of projectors status on built-in display Operating system updatable via DTS RED BOX

I OPERATING AMBIENT TEMPERATURE I

-10° / 40°

| PHYSICAL |

3-unit rack-mountable sturdy metal case covered with epoxy paint Protection rating: IP20 Dimensions: 480 x 496 x 131 h mm Weight: 13.8 Kg