



Epix Line 10 IP 10-Pack Road Case

A rolling road case that includes 10 EPIX Line 10 IP fixtures with all accessories, clamps, and multiple filter options. The case can be configured to hold up to 20 fixtures.

- Rolling case packed with 10pcs Epix Line 10 IP fixtures packed with all accessories included single pack fixtures; 2x clamps installed on each fixture
- Ability to remove additional light filters to pack 10-more Epix Line 10 IP fixtures (20-total per case)

SPECIFICATIONS

Optical

Light Source: 100 SMD 2727LEDs (tri-color RGB), 50,000 hours life expectancy

Beam Angle (open optics): 115.2°

Field Angle (open optics): 163°

Viewing Angle (open optics): 171.6°

Lumens:

open optics: 1,538

square milky white optics: 784

square black stealth optics: 239

round milky white optics: 943

Pixel Pitch: 10 mm

Display Refresh Rate: 4,900 Hz

Dynamic Effects

Strobe Rate: 0 to 30 Hz

Construction / Physical

Dimensions:

no filter: 39.37 x 1.161 x 2.862 in (1,000 x 29.5 x 72.7 mm)

square filter installed: 39.37 x 1.228 x 2.953 in (1,000 x 31.20 x 75 mm)

round filter installed: 39.37 x 1.969 x 4.63 in (1,000 x 50 x 117.6 mm)

road case: 47.2 x 23.6 x 29.6 in (1200 x 600 x 752 mm)

Weight: 176 lb (79.8 kg)

Exterior Color: Black

Housing Material: Aluminum alloy, Aluminum die-cast, High-impact flame-retardant polymer, Steel

Connections

Power Supply (remote driver): Epix D4 IP

Physical Linking (Standard Mode): 10 inline EPIX Line 10 IP

Physical Linking (Hi Power Mode): 6 inline EPIX Line 10 IP

Data Connectors: 4-pin IP65 XLR

Minimum required device linking cable size: 4 conductor (2 x 14 AWG, 2 x 16 AWG)

Cable Shielding: compatible with both shielded and unshielded cables

Control

DMX Channels: 2, 18, Groups of 5/10/25/50, or 300

Electrical

Input Voltage: 48 VDC

Power and Current (Standard): 21 W, .44 A @ 48 VDC

Power and Current (Hi Power): 32 W, .671 A @ 48 VDC

Required Accessories

KLSTR Software

Epix D4 IP Controller

Optional Accessories

EPIXMNTSPIGOT (Epix Mounting Bracket: Spigot Adapter 28mm)

EPIXMNTANGLE (Epix Mounting Bracket: +/- 120° Angling Adapter)

M12/1/2" BOLT

Clamps

RIGLINK 4-PIN XLR Cables

What's Included

10 EPIX LINE 10 IP
10 INTERLOCKING BRACKET
10 MILKY WHITE SQUARE FILTER (INSTALLED)
10 BLACK STEALTH SQUARE FILTER (INCLUDED)
10 MILKY WHITE ROUND FILTER (INCLUDED)
20 MOUNTING BRACKETS (INSTALLED)
Road case
power cords
power linking cord
IEC power cord
Local plug to proprietary IP66 input power cord
signal linking cord
Male/female 3/5-pin XLR DMX to proprietary adapters
Gel frame holder
Gel frame
Controllers: IRC, FCW, ACW, FCT, FCM
Omega bracket with mounting hardware