

Name	Club Series MKII
Properties	Analog
Properties	OFC oxygen free copper
Application area	Studio / Broadcast
Application area	Stage / live
Application area	ELA 100 V
Application area	Installation
Application	Microphone Cable
Colour	black
Colour detailed	black
Signal transmission	symmetrical
Construction	(2LI2Y0,34mm²)CY
Jacket material	PVC
Jacket Ø [mm]	6,50
Number of Channels (audio)	1
Inner conductor (audio)	2
Inner conductor (audio) [mm²]	0,34
Inner conductor Ø (audio) [mm]	0,66
AWG (audio)	22
Shielding	Copper braided shielding with 0.10 mm indiv. strands
Copper strands (audio)	19
Copper strand Ø (audio) [mm]	0,15
Conductor insulation material	PE
Conductor insulation Ø [mm]	1,50
Weight per 1 m [g]	50
UV-resistant	yes
Fire load per m [kWh]	0,22
Style variant	round
Shielding factor [%]	95
Packing	100 m spool
Packing	500 m spool
Temperature min. [°C]	-25
Temperature max. [°C]	70
Width [mm]	6,5
Height [mm]	6,5
Capac. cond./cond. per 1 m (audio) [pF]	58
Capacity wire/wire at 1 ft. (audio) [pF]	17,6784
Capac. cond./shield. per 1 m (audio) [pF]	115
Capacity wire/electic screen at 1 ft. (audio) [pF]	35,052
Impedance [Ω]	100
Insulation resist. per 1 km [GΩ]	1
Insulation resist. per 1000 feet [GΩ]	0,3048
Insulation resist. per 1 km (audio) [GΩ]	1
Insulation resist. per 1000 feet (audio) [GΩ]	0,3048
Conductor resistance per 1 km [Ω]	55
Conductor resistance per 1000 ft. [Ω]	16,764
Shield. resistance per 1 km [Ω]	25
Shield. resistance per 1000 ft. [Ω]	7,62
EAN	4049371001915