

Monofilament polyester braided sleeving



CHARACTERISTICS

- Temperature class : F
- Continuous working temperature : from -50°C to +155°C. Peaks at +180°C
- Halogen free
- Flammability : self-extinguishing
- Good mechanical resistance
- Excellent resistance to abrasion
- Good resistance to solvent
- Non watertight
- Very flexible
- Expansion ratio : from 1 to 2
- Use : Hot cutting to avoid fraying

STANDARDS*

- Compliant with RoHS directive
- Compliant with Reach regulation
- EN 60684-3 sheets 340 to 342 (4-2003)
- EN 60684-1 (10-2003)
- EN 60684-2 (07-2012)

COLOURS AND PACKAGINGS

- Manufactured diameters : from 3 to 60 mm
- Standard colour : Black or grey

Standard packaging : Rolls

- Diameter 3 to 10 mm : 100 m
- Diameter 12 to 20 mm : 50 m
- Diameter 25 to 60 mm : 25 m

Other packaging : Bobbins

- Diameter 3 to 4 mm : 500 m
- Diameter 5 to 6 mm : 400 m
- Diameter 8 to 10 mm : 300 m
- Diameter 12 to 15 mm : 250 m
- Diameter 20 to 25 mm : 200 m
- Diameter 30 mm : 150 m
- Diameter 40 to 60 mm : 100 m

APPLICATIONS



Inner nominal diameter (mm)	3	4	5	6	8	10	12	15	20	25	30	40	50	60
Inner maximal diameter (mm)	6	8.5	10.5	12	15	19	22	25	30	38	49	64	70	84

* Our products pass all or parts of requirements for the above-mentioned standards. The technical information written on our datasheets correspond to the most recent knowledges we have on those products. but the user is not exempted to verify the performances in the real particular context of application.