

Name	SC-Square 4-Core MKII
Properties	OFC oxygen free copper
Properties	Analog
Application area	Mobile outdoor / indoor
Application area	Stage / live
Application area	Installation
Application	Microphone Cable
Colour	black
Colour detailed	black
Signal transmission	symmetrical
Construction	(4LI2Y0,20mm²)(ST)DY
Jacket material	PVC
Jacket Ø [mm]	6,50
Number of Channels (audio)	1
Inner conductor (audio)	4
Inner conductor (audio) [mm²]	0,20
Inner conductor Ø (audio) [mm]	0,50
AWG (audio)	24
Shielding	Copper spiral shielding tin-plated + conductive fleece-foil
Copper strands (audio)	102
Copper strand Ø (audio) [mm]	0,05
Conductor insulation material	PE
Weight per 1 m [g]	53
UV-resistant	yes
Fire load per m [kWh]	0,22
Style variant	round
Shielding factor [%]	100
Packing	500 m spool
Packing	100 m spool
Temperature min. [°C]	-25
Temperature max. [°C]	70
Width [mm]	6,5
Height [mm]	6,5
Capac. cond./cond. per 1 m (audio) [pF]	65
Capacity wire/wire at 1 ft. (audio) [pF]	19,812
Capac. cond./shield. per 1 m (audio) [pF]	120
Capacity wire/electic screen at 1 ft. (audio) [pF]	36,576
Impedance [Ω]	95
Insulation resist. per 1 km [GΩ]	0,2
Insulation resist. per 1000 feet [GΩ]	0,061
Insulation resist. per 1 km (audio) [GΩ]	0,2
Insulation resist. per 1000 feet (audio) [GΩ]	0,061
Conductor resistance per 1 km [Ω]	98
Conductor resistance per 1000 ft. [Ω]	29,8704
Shield. resistance per 1 km [Ω]	20
Shield. resistance per 1000 ft. [Ω]	6,096
EAN	4049371001991