

Name	SC-Classique
Properties	Analog
Properties	OFC oxygen free copper
Application area	Stage / live
Application area	Studio / Broadcast
Application area	Mobile outdoor / indoor
Application	Instrument Cable
Colour	blue
Colour	black
Colour detailed	black-blue
Signal transmission	asymmetrical
Construction	LI2Y(LS)CY1x0,50mm ²
Jacket material	PVC + fabric
Jacket Ø [mm]	6,50
Number of Channels (audio)	1
Inner conductor (audio)	1
Inner conductor (audio) [mm ²]	0,50
Inner conductor Ø (audio) [mm]	0,80
AWG (audio)	20
Shielding	Copper spiral tin-plated + semiconductor
Copper strands (audio)	28
Copper strand Ø (audio) [mm]	0,15
Conductor insulation material	Foam / Skin-PE
Conductor insulation Ø [mm]	2,20
Weight per 1 m [g]	54
Fire load per m [kWh]	0,26
Style variant	round
Shielding factor [%]	100
Packing	100 m spool
Temperature min. [°C]	-40
Temperature max. [°C]	80
Width [mm]	6,5
Height [mm]	6,5
Capac. cond./shield. per 1 m (audio) [pF]	78
Capacity wire/electic screen at 1 ft. (audio) [pF]	23,7744
Insulation resist. per 1 km [GΩ]	0,01
Insulation resist. per 1000 feet [GΩ]	0,003
Insulation resist. per 1 km (audio) [GΩ]	0,01
Insulation resist. per 1000 feet (audio) [GΩ]	0,003
Conductor resistance per 1 km [Ω]	36
Conductor resistance per 1000 ft. [Ω]	10,9728
EAN	4049371004664