

Name	SC-Isopod SO-F22
Properties	OFC oxygen free copper
Properties	Analog
Application area	Installation
Application	Patch cable
Colour	black
Colour detailed	black
Signal transmission	symmetrical
Construction	(2LI2Y0,22mm²)(ST)Y
Jacket material	PVC
Jacket Ø [mm]	3,30
Number of Channels (audio)	1
Inner conductor (audio)	2
Inner conductor (audio) [mm²]	0,22
Inner conductor Ø (audio) [mm]	0,53
AWG (audio)	24
Shielding	AL / PT foil + AL / PT foil + filler strand, tin-plated
Copper strands (audio)	7
Copper strand Ø (audio) [mm]	0,20
Conductor insulation material	PE
Conductor insulation Ø [mm]	1,12
Weight per 1 m [g]	16
UV-resistant	yes
Fire load per m [kWh]	0,05
Style variant	round
Shielding factor [%]	100
Packing	200 m spool
Temperature min. [°C]	-25
Temperature max. [°C]	70
Width [mm]	3,3
Height [mm]	3,3
Capac. cond./cond. per 1 m (audio) [pF]	74
Capacity wire/wire at 1 ft. (audio) [pF]	22,5552
Capac. cond./shield. per 1 m (audio) [pF]	143
Capacity wire/electic screen at 1 ft. (audio) [pF]	43,5864
Insulation resist. per 1 km [GΩ]	0,2
Insulation resist. per 1000 feet [GΩ]	0,061
Insulation resist. per 1 km (audio) [GΩ]	0,2
Insulation resist. per 1000 feet (audio) [GΩ]	0,061
Conductor resistance per 1 km [Ω]	88
Conductor resistance per 1000 ft. [Ω]	26,8224
Shield. resistance per 1 km [Ω]	75
Shield. resistance per 1000 ft. [Ω]	22,86
EAN	4049371004480