

Nexans ref.: 3X2.5H07

EAN 13: 3427680014627

Industrial flexible cable, insulation and outer sheath in elastomer.  
Oil resistant, flame retardant according to IEC/EN 60332-1-2 standard. H07RN-F

## DESCRIPTION

### Application

The TITANEX® flexible rubber cable range offers exceptional performances and is designed to release you from all your constraints. Robust yet flexible, TITANEX® is easy to use and withstands the toughest of conditions, such as hard-wearing situations, extreme temperatures and most chemicals. For more than 50 years the TITANEX® cable range properties have been recognized as the best choice for all mobile and fixed installations in industrial environments such as construction sites, cranes, machines tools, factories, generators etc.

TITANEX® is also suitable for public environments and temporary events such as festivals or sports competitions, where the cable is often laid directly on the ground with no protection.

The cable may be rated 0,6/1 kV where the installation has built-in protection and for motors in lifting appliances - machine tools - etc.

### Installation

This cable can be installed in open air or be buried but with extra mechanical protection.

### Conductors laid up

Assembled conductors.

**NEW ! Marking :** The cross section marking is enlarged to allow easy identification during installation.

USE  $\langle \text{har} \rangle N (x \text{ or } G) S$  TITANEX®

- N = Number of conductor
- G = with Green/Yellow
- x = without Green/Yellow
- S = cross-section en mm<sup>2</sup>



## DECLARATION OF PERFORMANCE

Reaction to fire: E<sub>ca</sub>  
according to EN50575:2014  
+A1:2016

## STANDARDS

**International** EN 50525-2-21;  
HD 22.4; HD 516;  
IEC 60245-4 type 66

**National** NF C 32-102-4



Reaction to fire  
E<sub>ca</sub>



Conductor flexibility  
Flexible class 5



Lead free  
Yes



Rated Voltage U<sub>o</sub>/U  
(U<sub>m</sub>)  
450 / 750 V



Mechanical  
resistance to  
impacts  
AG3



Cable flexibility  
Flexible



Chemical  
resistance  
Accidental



Water proof  
Good

**CHARACTERISTICS****Construction characteristics**

Conductor material	Bare copper
Conductor flexibility	Flexible class 5
Insulation	Special cross-linked elastomer
Outer sheath	Special cross-linked elastomer
Sheath colour	Black
Lead free	Yes
With Green/Yellow core	Yes
With smaller neutral conductor	No

**Dimensional characteristics**

Number of cores	3
Conductor cross-section	2.5 mm <sup>2</sup>
Minimum outer diameter	10.9 mm
Maximum outer diameter	14.0 mm
Approximate weight	195 kg/km

**Electrical characteristics**

Rated Voltage U <sub>0</sub> /U (U <sub>m</sub> )	450 / 750 V
Voltage drop, single phase	16.2 V/A.km
Permissible current rating in open air	36 A

**Mechanical characteristics**

Mechanical resistance to impacts	AG3
Cable flexibility	Flexible

**Usage characteristics**

Silicone free	Yes
Chemical resistance	Accidental
Water proof	Good
Flame retardant	C2, NF C 32-070 & IEC 60332-1
Packaging	Cut to length
Operating temperature, range	-25 .. 55 °C
Minimum static operating bending radius	42 mm
Minimum dynamic operating bending radius	84.0 mm
Max. conductor temperature in service	90 °C
Short-circuit max. conductor temperature	200 °C
Oil resistance	Yes
RoHS compliant	Yes

**NEW CORES IDENTIFICATION**

Core identification in accordance with HD 308 S2 - Identification of cores in cables and flexible cords.

Number of cores	HD 308 S2 since january 2004	
	G (earth core)	X (without earth core)
1		Black (preferential)

All drawings, designs, specifications, plans and particulars of weights, size and dimensions contained in the technical or commercial documentation of Nexans is indicative only and shall not be binding on Nexans or be treated as constituting a representation on the part of Nexans.

Generated 10/07/18 www.nexans.co.uk Page 2 / 3

2		Blue + Brown
3*	Green - Yellow + Blue + Brown	Brown + Black + Grey
3**		Blue + Brown + Black
4	Green - Yellow + Brown + Black + Grey	Blue + Brown + Black + Grey
5	Green - Yellow + Blue + Brown + Black + Grey	Blue + Brown + Black + Grey + Black
> 5	White printed numbers + 1 Green - Yellow	White printed numbers
* For the cables without Green/Yellow with a cross-section >4mm <sup>2</sup>		
** For the cables without Green/Yellow with a cross-section of 1,5mm <sup>2</sup> & 2,5mm <sup>2</sup>		

## COMPLEMENTS

### Maximum Operating Temperature

Fixed and protected installation: 90°C

Mobile installation: 60°C

In short-circuit: 200°C

### Minimum bending radius

- Dynamic use: 6 to 8x cable outer diameter
- Static use: 3x outer cable diameter if the outer diam is < or =12mm,  
4x outer cable diameter if the outer diam is >12mm.

### NEW! PACKAGING

- Improved labelling for easy identification of the product
- Key features and specifications highlighted
- Scan QR code to get full technical specifications