



GE
Lighting



5040
kWh/1000h

C
energy class

27
lumens/watt

Single Ended Halogen CP29 240V

88876

Product information

Quartzline® lamps designed for optimum performance in today's precision range of stage, studio and architectural luminaires. Full range up to 24,000 W
-Range of bases to meet the needs of OEMs -
Chromised seal protection up to 500° C.

ENERGY LABEL: Y IJA / IE IA
 энергия · ενέργεια
 GE Lighting 88876 CP29 240V
 Energy efficiency class: C
 Consumption: 5040 kWh/1000h

Application areas

- Film and Broadcast
- Theatre



Product data

Product Code	88876
Bulb Shape	Globe
Bulb Diameter [mm]	65
Maximum Overall Length [mm]	280
Light Center Length [mm]	165
Net weight per piece [g]	350
Gross weight per piece [g]	600
Brand	General Electric (GE)
Cap/Base	G38

Performance data

Weighted energy consumption [kWh/1000h]	5040
Energy efficiency class (EEC)	C
Rated Life [h]	375
Nominal correlated colour temperature (CCT) [K]	3200
Nominal lumens [lm]	135000
Colour Rendering Index (CRI) [Ra]	100

Electrical data

Coil type	C-13
Dimming Capability	Yes
Ballast Required	No
Nominal power [W]	5000
Nominal lamp voltage [V]	240

Logistic data

DUN Code	10043168888766
EAN Code	0043168888769
Pack Quantity	1
Inner pack type	BOX
Outer pack type	OUTER BOX
Layer quantity	18 EUR, 23 UK
Layer quantity EUR	18
Layer quantity UK	23
Pallet quantity EUR (PC)	126
Pallet quantity UK (PC)	161
Outer case size	340 x 135 x 140 (mm)
Product status	Available

Downloads & Links

[Go to the catalog site \(HTTP\)](#)

[Entertainment Solution Spectrum Catalogue \(PDF\)](#)

[Lighting design tools & calculators \(HTTP\)](#)

[High-res images / Technical drawings \(HTTP\)](#)

[Certificate for the Quality Management System of GE Lighting EMEA \(PDF\)](#)

[Certificate for the Environmental Management System of GE Lighting EMEA \(PDF\)](#)

Disclaimer

Special Purpose Lamp, Not suited for household illumination