

PROFILO LED 80 CT



The compact LED
Profile with
selectable color
temperature, for
Theatre and
Television

LINEARLY TUNABLE WHITE COLOR
TEMPERATURE (2700K – 6000K)

INTERNAL 4-SHUTTER SHAPING
SYSTEM

FLICKER FREE

ADJUSTABLE ZOOM 20° - 36°

NOISELESS

DMX CONTROL

EASY MAINTENANCE

LONG LIFE LED
(50,000 HOURS)



PROFILO LED 80 CT is a very compact LED profile spot equipped with an high efficiency 100 W white LED source.

The unit LED's white color temperature is linearly tunable from 2700K to 6000K; a must in top level Television and Theatre applications, where a perfectly adjustable white color temperature is a key requirement.

The unit features an internal four-shutter shaping system, and a 20° to 36° linear zoom.



PROFILO LED 80 CT



OUTPUT

Single high-power white LED with linearly tunable color temperature (2700K – 6000K)
LED lifespan: 50,000 hours

OPTICAL GROUP

20° - 36° linear zoom; High definition zoom lens with double optical condenser lens

INTERFACE / CONTROL / PROGRAMMING

Interface: DMX 512 / RDM
7 DMX channels (default) or 2 DMX channels
4-digit 7-segment LED display

POWER SUPPLY

Electronic full-range 100-240 Vac 50 / 60 Hz
Power consumption: 100 W max

CONNECTORS

Power supply: PowerCON In/Out;
DMX: XLR 5-pole In/Out

OPERATING AMBIENT TEMPERATURE

-10° / 40°

PHYSICAL

Weight: 5.8 Kg
Dimensions: 250x434x302 H mm
Internal system with four removable shutters
Strong housing with folded edges

INTERNATIONAL CERTIFICATIONS

CE certification

INCLUDED ITEMS

1 x PowerCON female cable connector (code 0520P014)
1 x XLR 5 pins male cable connector (code 0508B028)
1 x XLR 5 pins female cable connector (code 0508B027)
1 x Filterframe - Black finish - already installed on the projector (code 02M00422.46)
4 x Shutter blades (single blade code 02SK0041)

