



# MSR Short Arc

## MSR 1200 SA 1CT/4

The lamp's short arc and compact design helps enable a compact luminaire that provides high beam intensity, while the excellent color rendition characteristics help ensure optimal colors on stage. The highly innovative P3 technology, developed by Philips, allows MSR Short Arc lamps to be used at higher temperatures in any burning position. The result? Longer lifetime, fewer early failures and a highly consistent performance throughout the lamp's lifetime.

### Product data


General Information	
Cap-Base	GY22 [ GY22]
Operating Position	UNIVERSAL [ Any or Universal (U)]
Main Application	Studio/Disco
Life To 50% Failures (Nom)	750 h
System Description	Short Arc
Light Technical	
Color Code	- [ Not Specified]
Luminous Flux (Min)	80000 lm
Luminous Flux (Nom)	96000 lm
Chromaticity Coordinate X (Nom)	323
Chromaticity Coordinate Y (Nom)	328
Correlated Color Temperature (Nom)	6000 K
Luminous Efficacy (rated) (Nom)	80 lm/W
Color Rendering Index (Nom)	80
Operating and Electrical	
Power (Rated) (Nom)	1200 W
Lamp Current (Nom)	13.8 A

Ignition Supply Voltage (Min)	207 V
Controls and Dimming	
Dimmable	No
Mechanical and Housing	
Cap-Base Information	-
Luminaire Design Requirements	
Bulb Temperature (Max)	1000 °C
Pinch Temperature (Max)	500 °C
Product Data	
Full product code	871829122125800
Order product name	MSR 1200 SA 1CT/4
EAN/UPC - Product	8718291221258
Order code	928170905115
Numerator - Quantity Per Pack	1
Numerator - Packs per outer box	4
Material Nr. (12NC)	928170905115

MSR Short Arc

Net Weight (Piece)	0.096 kg
--------------------	----------

Dimensional drawing



MSR 1200 SA

Product	D	O	L	L	L	C
---------	---	---	---	---	---	---

