



Discharge - Single Ended Hot Restrike csr 4000se/HR/UV- c 27765

Product information

Compact, single ended metal halide hot restrike lamps for a variety of applications requiring high luminance, reliability and excellent colour characteristics. Excellent colour rendering, Ra>90, and high CCT 5600–6000 K with superior colour stability- Universal burn position with hot restrike capability- High efficiency with excellent lumen maintenance -Available with UV blocking.


Application areas



Film and Broadcast











Product data

Product Code	27765
Bulb Shape	Globe
Bulb Finish	Clear
Bulb Diameter [mm]	75
Maximum Overall Length [mm]	260
Light Center Length [mm]	142
Arc Gap	24
Net weight per piece [g]	353
Gross weight per piece [g]	743
Operating position	U - Universal
Brand	General Electric (GE)
Cap/Base	G38

Performance data

Colour Code	956
Weighted energy consumption [kWh/1000h]	4400
Energy efficiency class (EEC)	A+
Nominal chromaticity coordinate X	0.33
Nominal chromaticity coordinate Y	0.325
Nominal correlated colour temperature (CCT) [K]]	6000
Nominal lumens [lm]	380000
Colour Rendering Index (CRI) [Ra]	90

Electrical data

Lamp Current [A]	20
Dimming Capability	No
Ballast Required	Yes
Nominal power [W]	4000
Nominal lamp voltage [V]	200





Logistic data

DUN Code	10043168277652
EAN Code	0043168277655
Pack Quantity	6
Inner pack type	BOX
Outer pack type	OUTER BOX
Layer quantity	36 EUR, 36 UK
Layer quantity EUR	36
Layer quantity UK	36
Pallet quantity EUR (PC)	108
Pallet quantity UK (PC)	108
Outer case size	415 x 270 x 360 (mm)
Product status	Available

Downloads & Links Go to the catalog site (HTTP) Entertainment Solution Spectrum Catalogue (PDF) Lighting design tools & calculators (HTTP) High-res images / Technical drawings (HTTP) Certificate for the Quality Management System of GE Lighting EMEA (PDF) Certificate for the Environmental Management System of GE Lighting EMEA (PDF)

Disclaimer

Special Purpose Lamp, Not suited for household illumination