



MSR

MSR 400 1CT/4


The high color rendering index of the single ended MSR series ensures that everyone in the audience can enjoy the true colors of the scenery, the stage props, the players and their costumes – in fact everything that is on stage can be made bright and vivid in daylight quality light. Also, thanks to the single ended lamp concept, the luminaire has optimal light collection and direction possibilities to help ensure brightness on stage exactly where and when it is needed. In addition, the MSR can be used in any burning position for easy set-up and convenience.

Product data

General Information		Lamp Current (Nom)		6.9 A
Cap-Base	GX9.5 [GX9.5]	Ignition Supply Voltage (Min)		207 V
Operating Position	UNIVERSAL [Any or Universal (U)]	Controls and Dimming		
Main Application	Studio/Disco	Dimmable		No
Life To 50% Failures (Nom)	1000 h	Mechanical and Housing		
System Description	Cold Strike	Cap-Base Information		-
Light Technical		Luminaire Design Requirements		
Color Code	- [Not Specified]	Bulb Temperature (Max)		700 °C
Luminous Flux (Min)	28500 lm	Pinch Temperature (Max)		350 °C
Luminous Flux (Nom)	32000 lm	Product Data		
Chromaticity Coordinate X (Nom)	325	Full product code		871869641600600
Chromaticity Coordinate Y (Nom)	320	Order product name		MSR 400 1CT/4
Correlated Color Temperature (Nom)	5900 K	EAN/UPC - Product		8718696416006
Luminous Efficacy (rated) (Nom)	80 lm/W	Order code		928077905115
Color Rendering Index (Nom)	95	Numerator - Quantity Per Pack		1
Operating and Electrical				
Power (Rated) (Nom)	400 W			

Numerator - Packs per outer box	4
Material Nr. (12NC)	928077905115
Net Weight (Piece)	44.000 g

Dimensional drawing



MSR 400

Product	D	O	L	L	L	C	F	F	F
MSR 400 1CT/4	23 mm	6.0 mm	61 mm	63 mm	62 mm	112 mm	36 mm	35 mm	34 mm

