

Name	SC-Orbit 225 MKII, HighEnd
Properties	Analog
Properties	OFC oxygen free copper
Application area	Installation
Application area	Studio / Broadcast
Application	Speaker Cable
Colour	black
Colour	transparent
Colour detailed	black transparent
Construction	2LIY2,50mm²
Jacket material	PVC
Jacket Ø [mm]	0,00
Number of Channels (audio)	1
Inner conductor (audio)	2
Inner conductor (audio) [mm²]	2,50
Inner conductor Ø (audio) [mm]	1,78
AWG (audio)	13
Copper strands (audio)	651
Copper strand Ø (audio) [mm]	0,07
Weight per 1 m [g]	90
UV-resistant	yes
Fire load per m [kWh]	0,17
Style variant	twin
Packing	100 m spool
Temperature min. [°C]	-30
Temperature max. [°C]	70
Width [mm]	10,2
Height [mm]	4,8
Capac. cond./cond. per 1 m (audio) [pF]	60
Capacity wire/wire at 1 ft. (audio) [pF]	18,288
Insulation resist. per 1 km [GΩ]	0,01
Insulation resist. per 1000 feet [GΩ]	0,003
Insulation resist. per 1 km (audio) [GΩ]	0,01
Insulation resist. per 1000 feet (audio) [GΩ]	0,003
Conductor resistance per 1 km [Ω]	7,8
Conductor resistance per 1000 ft. [Ω]	2,3774
EAN	4049371002967