# HPL 93729 750 W 230 V

HPL | High-performance lamps

### Product benefits

- Optimum use of the generated light in the spotlight

## Technical data

### Electrical data

| | |
|---|---|
| **Nominal wattage** | 750.00 W |
| **Nominal voltage** | 230 V |

### Photometrical data

| | |
|---|---|
| **Color temperature** | 3200 K |

### Dimensions & weight

| | |
|---|---|
| **Diameter** | 19.0 mm |
| **Length** | 101.0 mm |
| **Length with base excl. base pins/connection** | 104.00 mm |
| **Light center length (LCL)** | 60.3 mm |
| **Illuminated field** | 7.5*11.5 mm² [1] |

[1] Type of filament 6-C8

### Lifespan

| | |
|---|---|
| **Lifespan** | 300 h |

### Additional product data

| | |
|---|---|
| **Base (standard designation)** | 2 pins |

### Capabilities

| | |
|---|---|
| **Burning position** | Any |

### Certificates & standards

| | |
|---|---|
| **EEI – Energy Label** | B |

## Country specific categorizations

| Order reference | 93729 750W 230V |
|---|---|

### Country specific information

| Product code | METEL code | SEG-No. | STK-Number | UK Org |
|---|---|---|---|---|
| 4050300654201 | OSRH93729 | - | - | - |

# Product datasheet

## Safety advice

To prevent personal injury or damage to property, halogen lamps may only be operated in suitable luminaires designed with suitable mechanisms (cover panel etc.) to ensure that in the event of a lamp bursting no parts/shards can escape and that during operation no ultraviolet radiation can escape. Because of the heat produced only heat-resistant lamp connections (holders) may be used. Do not operate near people, or any materials that are flammable, sensitive to heat or affected by drying out. Detailed information is available on request.

## Logistical Data

| Product code | Product description | Packaging unit (Pieces/Unit) | Dimensions (length x width x height) | Volume | Gross weight |
|---|---|---|---|---|---|
| 4050300654201 | HPL 93729 750 W 230 V | Folding carton box 1 | 131 mm x 42 mm x 46 mm | 0.25 dm³ | 77.00 g |
| 4050300654218 | HPL 93729 750 W 230 V | Shipping carton box 12 | 174 mm x 148 mm x 145 mm | 3.73 dm³ | 953.00 g |

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

## Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.

—