

Name	SC-Onyx 2025 MKII
Properties	OFC oxygen free copper
Properties	Analog
Application area	Installation
Application area	Studio / Broadcast
Application	Patch & Instrument Cable
Colour	black
Colour detailed	black
Signal transmission	asymmetrical
Construction	LI2YDY2x0,25mm ²
Jacket material	PVC
Number of Channels (audio)	2
Inner conductor (audio)	1
Inner conductor (audio) [mm ²]	0,25
Inner conductor Ø (audio) [mm]	0,56
AWG (audio)	24
Shielding	Copper spiral shielding
Copper strands (audio)	32
Copper strand Ø (audio) [mm]	0,10
Conductor insulation material	PE
Weight per 1 m [g]	38
UV-resistant	yes
Fire load per m [kWh]	0,23
Style variant	round
Shielding factor [%]	90
Packing	100 m spool
Temperature min. [°C]	-20
Temperature max. [°C]	70
Width [mm]	8,3
Height [mm]	3,8
Capac. cond./shield. per 1 m (audio) [pF]	120
Capacity wire/electic screen at 1 ft. (audio) [pF]	36,576
Insulation resist. per 1 km [GΩ]	1
Insulation resist. per 1000 feet [GΩ]	0,3048
Insulation resist. per 1 km (audio) [GΩ]	1
Insulation resist. per 1000 feet (audio) [GΩ]	0,3048
Conductor resistance per 1 km [Ω]	115
Conductor resistance per 1000 ft. [Ω]	35,052
EAN	4049371003292